



NUMBER	ITEMS	N/A	NOT SATISFIED	SATISFIED	LOCATION IN E.D.S. & P.M.
1.	Vicinity Map				<u>G-3112</u>
2.	City of Goodyear Dry Utility Notes				0.4.1, 2.11.1(H), 2.11.4(A), G-3112
3.	Symbol and Abbreviation legend on plans				2.11.2(D), 2.11.3(C.17)
	Plans are Legible & Reproducible. Use min font for $\frac{1}{2}$ size reproduction.				2.11.2(N)
5.	Blue stake note every sheet				2.11.2(R), <u>G-3112</u>
6.	Plans shall have a north arrow and scale bar on all applicable sheets				2.11.2(K) A scale of 1" = 40' is suggested as a minimum
7.	Trench detail showing width and depth and, if applicable, number of conduit or pipe, including Non-MAG & Non-City details				
	Quantities of joint trench and non-joint trench identified as 'IN R/W & PUE' and total square yardage of pavement replacement				
Ge	neral				
9.	Show & Dimension all R/W, PUE, and record easements including curb, sidewalk, and underground utilities				
10.	Stationing along monument line referenced to closest existing monument				
	Offset dimensions tied to monument lines in streets and/or to property lines in alleys and easements				
12.	Show all existing and proposed improvements and clearly indicate as such				
	Dimensions from center line of street to running line (every 500 feet minimum) and all alignment changes				
14.	Make sure that proposed utility and trench alignment does not conflict with retaining walls, fencing, driveways, water meter boxes trees				

Review Checklist



15.	Avoid installation of above-ground facilities within sight visibility triangles		<u>G-3228</u> , <u>G-3232</u>
16.	All above-ground equipment shall be clearly shown with location dimensioned. If necessary, details of above-ground equipment shall be included on plans		
17.	Check to see if project is part of a project that requires a Joint Trench permit. Individual Utility Company permits cannot be accepted or approved prior to the Joint Trench permit being approved		2.2.2(D)
18.	Proposed utility crossing shall be at 90-degree angle with the road or monument line		
19.	Street names clearly identified on plans		2.11.2(S)
20.	Plans drawn to scale adequate to accurately depict relationships among the physical features within the construction area and to identify potential conflicts		
21.	If proposed, utility will be located within an alley the location of any above-ground equipment; cannot interfere with the mobility of sanitation or maintenance vehicles		
22.	Proposed asphalt removal & replacement clearly illustrated on plans with dimensions for lineal feet and width; splice pit, boring and receiving pit, potholes and bell holes		
23.	Property addresses/lot numbers shown		2.11.2(S)
24.	For PGA North monitor wells, obtain prior approval from Public Works via email		
25.	On Scenic Arterials move running line to the outside 10' of R/W		G-3120
Co	ver & Separation		
26.	Check dry utility to wet utility minimum separation requirements		COG Detail G-3300
27.	Check horizontal clearances to utilities (min. 7' to hydrants for above ground equipment/facilities)		
28.	Check minimum coverage requirements table		48" under Art, 36" to 48" under minor Cull and Locals, 60" to 72" under future pavement, and 48" to 60" under future BC. See table on page 5





Mis	cellaneous		
29.	Trenching for utilities shall not start until all project related sewer, water, reclaimed water, and storm drain improvements are installed, backfilled, tested, and approved by the City Inspector.		2.3.4(E)
30.	Potholes are considered a pavement cut and pavement cut fees apply		 Pavement Cut Ordinance No. 2000-697 Paragraph 1. Add to the CPFS and cover sheet
31.	Check location of proposed utility in relationship to proposed or approved improvement plans to avoid creating conflicts between projects (pay close attention to proposed utilities at intersections that may require relocation at a future date due to roadway expansion)		
32.	Above-ground equipment and buried utilities at arterial/arterial and arterial/collector intersections shall not encroach into the dry utility clear zone		COG Detail G-3210-2
33.	Every effort shall be made to avoid cutting pavement. Unless otherwise approved by City Engineer, all new, reconstructed, renovated, or newly resurfaced pavement shall not cut for a period of 5 years from date of pavement acceptance by the City. In the event that a street opening cannot be avoided during the 5-year period a fee to cover damages and early deterioration will be assessed and added to the Construction Permit Fee Schedule		
34.	If proposed alignment includes a bore across COG Streets a bore profile must be provided on the plans and minimum 2-foot vertical clearance must be shown from other utilities		

Review Checklist



		Minimum (Coverage	Requiren	nents*		
			Develope	Undeveloped			
		Arterials and Mo	ajor Collectors	Minor Collecto	or and Locals	All Co	ases
ltem	Description	Under Existing and Future Pavement and Curb	Future Back of Curb	Under Existing and Future Pavement and Curb	Future Back of Curb	Under Existing and Future Pavement and Curb	Future Back of Curb
	0-600 volts	48"	48"	36"	36"	60"	48"
	601-7200 volts	48"	48"	42"	42"	66"	54"
Power	12KV (local Dist)	48"	48"	42"	42"	66"	54"
	12KV+ (30 feeder)	48"	48"	48"	48''	72"	60"
	Street Light	48"	48"	36"	36"	60"	48"
	Services	48"	48"	36"	36"	60''	48"
Gas	1" - 6" diameter	48"	48"	36"	36"	60''	48"
	>6" diameter	48"	48"	36"	36"	60"	48"
Telecom	Trunk lines	48"	48"	48"	48''	72"	60"
	Copper Services	48"	48"	36"	36"	60"	48"
CATV	Other	48"	48"	36"	36"	60"	48"
	Coaxial	48"	48"	36"	36"	60"	48"
Other Conduits		48"	48"	36"	36"	60''	48"

^{*} Jack and Bore shall be at minimum depth or 1' per 1" of conduit diameter, whichever is greater.

For facilities located in existing or proposed pavement. Cover is defined as the difference in elevation between the top of the line or pipe and the top of existing or proposed pavement.

For facilities outside of existing or proposed pavement. Cover is defined as the difference between the top of the line or pipe and the ultimate build out gutter grade of the roadway or re-graded ground surface, whichever is greater.

Review Checklist



APPLICATION TON DISTRICT A STORM WATER POLLUTION I ANT STARTED TH ID			PLANS (24x36" EXCEPT FOR SERVICE DROPS CAN BE 8.5"x11")		MER TRENCH	IRRIGATION DISTRICT APPROVAL	EASEMENT/ PUE DEDICATION	SWPPP (storm water pollution prevention)	CPFS (CONSTRUCTION PERMIT FEE SCHEDULE)	APPLICANT STARTED THE E-FORM PER THE SOP	FEES PAID	HTE# ASSIGNED (SUBDIVISIONS SHALL HAVE THE SAME HTE# AS THE CD'S)
PLANS G JOINT TI SWPPP G CPFS GO FEES PA				PERMIT APPLICATION	JOINT TRENCH/CUSTOMER TRENCH							
1. Subdivision \(\times \)	1. Subdivi:	sion	\boxtimes		\boxtimes				\boxtimes		\boxtimes	
2. Roadway Improvements	2. Roadw	ay Improvements	\boxtimes						\boxtimes	\boxtimes	\boxtimes	
3. Service Drops (individual service connections)	3. Service	Drops (individual service connections)	\boxtimes								\boxtimes	
4. Work on private property	4. Work or	n private property										
5.	5.											
Symbols Legend	Symbol	s Legend										
Required 🖂	Require	od										
Not Required	Not Red	quired										
May Be Required	Мау Ве	Required										

- Some plans might need to be separated into Off-site & On-site plan sets
 A SWPPP BMP's are required regardless of the size of land that will be disturbed by grading.